

**NuSil Technology**

1050 Cindy Lane • Carpinteria, CA 93013  
805/684-8780 • 805/566-9905 Fax  
www.nusil.com


An ISO 9001 Certified Company

# PLY-7532

Vinyl Endblocked Phenyl Copolymer

## Product Profile

### Description



- A clear, diphenyl dimethyl polysiloxane endblocked with reactive vinyl groups
- Other viscosities are available on a special order basis

### Applications

- For curing with crosslinkers and catalysts to form adhesives, sealant, rubbers and gels due to its reactive nature
- For extreme temperature stability

Typical Properties	Result	Metric Conv.	ASTM	NT-TM
Appearance	Translucent	-	D2090	002
Viscosity	1,300 cP	1,300 mPas	D1084, D2196	001
Specific Gravity	0.99	-	D792	003
Molecular Weight*	27,500	-	-	-
Non-Volatile Content	98.5%	-	D2288	004
Refractive Index	1.42	-	D1747, D1218	018
Flash Point	600°F	-	D92	092

\* Theoretical calculation

### Warnings About Product Safety

NuSil Technology believes that the information and data contained herein are accurate and reliable. However, the user is responsible to determine the material's suitability and safety of use. NuSil Technology cannot know each application's specific requirements and hereby notifies the user that it has not tested or determined this material's suitability or safety for use in any application. The user is responsible to adequately test and determine the safety and suitability for their application and NuSil Technology makes no warranty concerning fitness for any use or purpose. NuSil Technology has completed no testing to establish safety of use in any medical application.

NuSil Technology has tested this material only to determine if the product meets the applicable specifications. (Please contact NuSil Technology for assistance and recommendations when establishing specifications.) When considering the use of NuSil Technology products in a particular application, review the latest Material Safety Data Sheet and contact NuSil Technology with any questions about product safety information.

Do not use any chemical in a food, drug, cosmetic, or medical application or process until having determined the safety and legality of the use. The user is responsible to meet the requirements of the U.S. Food and Drug Administration (FDA) and any other regulatory agencies. Before handling any other materials mentioned in the text, obtain available product safety information and take the necessary steps to ensure safety of use.

#### Packaging

1 Pint (455 g)  
1 Gallon (3.64 kg)  
5 Gallon (18.2 kg)

#### Warranty

6 Months

## **Specifications**

Do not use the typical properties shown in this technical profile as a basis for preparing specifications. Please contact NuSil Technology for assistance and recommendations in establishing particular specifications.

## **Patent Warning**

NuSil Technology disclaims any expressed or implied warranty against the infringement of any patent. NuSil Technology does not warrant the use or sale of the products described herein will not infringe the claims of any United States' or other country's patents covering the product itself, its use in combination with other products or its use in the operation of any process.

## **Warranty Information**

NuSil Technology's warranty period is 6 months from the date of shipment when stored below 40°C in original unopened containers. Unless NuSil Technology provides a specific written warranty of fitness for a particular use, NuSil Technology's sole warranty is that the product will meet NuSil Technology's then current specification. NuSil Technology specifically disclaims any other expressed or implied warranty, including warranties of merchantability and fitness for use. The exclusive remedy and NuSil Technology's sole liability for breach of warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. NuSil Technology expressly disclaims any liability for incidental or consequential damages.



# **Polymer Systems** Technology Limited

## Silicone Sales & Services UK - Ireland - Benelux

© 2023 - **Polymer Systems Technology Limited™**

Unit 2. Network 4. Cressex Business Park,  
Lincoln Road, High Wycombe, Bucks. HP12 3RF

tel: +44 (0) 1494 446610

web: <https://www.silicone-polymers.com>

email: [sales@silicone-polymers.co.uk](mailto:sales@silicone-polymers.co.uk)

